LEADING PoE SOLUTIONs FOR IP SURVEILLANCE

PRODUCT GUIDE



www.aetektec.com

JAN, 2023

contents

Long Range PoE & Ethernet Product Guide — P3-13



- EPoH (Ethernet & Power over Hybrid Copper-Fiber Cable)
- EPoC (Ethernet & Power over Coax)
- EPoT (Ethernet & Power over UTP/STP)
- EPo2 (Ethernet & Power over 2 Wires)
- PoE Extender (Ethernet & Power over UTP/STP)

PoE Switch Product Guide — P14-22



- Outdoor IP67/IK10 PoE Switch
- Indoor PoE Switch
- Industrial PoE Switch

L2 PRO PoE Switch Product Guide — P23-32



- L2 PoE Switch
  - Outdoor IP67/IK10
  - Industrial
  - Indoor
- 10G L2 PRO Switch
  - Indoor
- L2 PRO PoE Switch
  - Outdoor IP67/IK10
  - Industrial
  - Indoor

Gigabit PoE Media Converter Product Guide — P33-35



- Media Converter
- PoE Media Converter
- PoE PD Media Converter

Gigabit PoE Injector Product Guide — P36-38



- Indoor Gigabit 60W/90W/95W PoE Injector
- Outdoor IP67/IK10 Gigabit 60W/90W/95W PoE Injector
- Industrial Gigabit 90W/95W PoE Injector

Gigabit PoE Extender Product Guide — P39-41



- Indoor Gigabit 90W PoE Extender
- Outdoor IP67/IK10 Gigabit 90W PoE Extender
- Indoor Gigabit 90W PoE Extender Plus
- Outdoor IP67/IK10 Gigabit 90W PoE Extender Plus

Gigabit PoE Surge Protector Product Guide — P42-44



- 1-CH Gigabit 802.3 bt/at/af PoE Surge Protector
- 4-CH/24-CH Gigabit 802.3 bt/at/af PoE Surge Protectors
- 4-CH/24-CH IP Managed Gigabit 802.3 bt/at/af PoE Surge Protectors

Outdoor Surveillance system — P45-48



- Back-up PoE Cabinet
- IP Back-up PoE Cabinet

Camera Housing Product Guide — P49-59



- AI Camera Housing
- AC24V (Optional DC24V)
- 802.3 bt/at/af PoE
- 800m PoE
- AISI 316L Stainless Steel

Illuminator Product Guide — P60-62



- Manual
- Motor
- Pulse Mode
- Affordable

Long Range PoE & Ethernet Product Guide

EPoH (Ethernet & Power over Hybrid Copper-Fiber Cable)
EPoC (Ethernet & Power over Coax)
EPoT (Ethernet & Power over UTP/STP)
EPo2 (Ethernet & Power over 2 Wires)
PoE Extender (Ethernet & Power over UTP/STP)





Long Range PoE & Ethernet Product Selection

1-CH 6-CH

over Hybrid copper-fiber cable

RX (Switch Site)

Base



HE10-110-RX P6

Chassis



CH-200 P6

TX (Camera Site)

IP67/IK10

PoE switch

30W at 60W/90W bt



H40-044-30-DC P6 P18
H40-082-30-DC P6 P18
H40-022-90-DC P6 P18
H40-044-91-DC P6 P18

L2 Switch



H51-044-30-DC P6 P28
H51-084-30-DC P6 P28
H51-044-91-DC P6 P28

L2 PRO Switch



H60-044-30-DC P6 P30
H60-084-30-DC P6 P30
H60-044-91-DC P6 P30

Industrial

PoE switch

30W at 60W/90W bt



D40-044-30-DC P6 P21
D40-082-30-DC P6 P21
D40-044-91-DC P6 P21

L2 Switch



D51-044-30-DC P6 P28
D51-084-30-DC P6 P28
D51-044-91-DC P6 P28

L2 PRO Switch



D60-044-30-DC P6 P30
D60-084-30-DC P6 P30
D60-044-91-DC P6 P30

Long Range PoE & Ethernet Product Selection

over Coax

RX (Switch Site)

		PoE In	100-240VAC In
Adapter	1-port	XE11-110-RX P10	XE10-110-RX P10
Switch	4-port	XC10-041-250 P9	
	8-port	XC10-084-380 P9	

TX (Camera Site)

		Indoor	IP67/IK10
Adapter	1-port	XE10-110-TX P10	XE22-110-TX P10
	2-port	XE12-120-TX P10	XE22-120-TX P10

		w/ IR LED	Heater & Blower	Thermal
Camera Housing	500m	A5020-E P10		
	600m		A5000-E P10	
	800m			A5100-E P10

over UTP/STP

RX (Switch Site)

		PoE In	100-240VAC In
Adapter	1-port	TE11-110-RX P11	TE10-110-RX P11
Switch	4-port	XT10-041-250 P11	

TX (Camera Site)

		Indoor	IP67/IK10
Adapter	1-port	TE10-110-TX P11	TE22-110-TX P12
	2-port	TE12-120-TX P12	TE22-120-TX P12

		w/ IR LED	Heater & Blower	Thermal
Camera Housing	500m	A5020-T P12		
	600m		A5000-T P12	
	800m			A5100-T P12

over 2 Wires

			Indoor	PoE In	100-240VAC In
RX (Switch Site)	Adapter	1-port		2E11-110-RX P13	2E10-110-RX P13
TX (Camera Site)	Adapter	1-port	2E10-110-TX P13		

Hybrid copper and fiber in one cable



Up to 12
optical fibers SMF or MMF

12 AWG (2 mm) or
16 AWG (1.3 mm)
Conductors

One Cable, More Possibilities

· The Hybrid cable combines fiber optic cable and copper power cable to extend 4xaf PoE distance up to 2,400m / 7,874ft.

Fiber Cable
· Long-Distance Data Transmission
· High Bandwidth

Copper Cable
· Long-Distance Power Transmission




Applications

· Optical LAN · Emergency Phones · 4K/HD security cameras · Digital signage
· Wi-Fi access points · Small cells · Virtually any IP PoE PD

One Channel Solution

AETEK HE10-110-RX
1-CH EPoH RX Base
(Gigabit Ethernet & Power over Hybrid Cable)


- Hybrid cable (from 3rd party)



Multi-Channel Solution

AETEK CH-200
Power & Fiber Distribution

- AETEK Fiber Ethernet Switch or 3rd party Fiber Switch
- High power supply w/ 48-57 VDC output (from 3rd party)
- Hybrid cable (from 3rd party)




Distance Chart

PoE (Data + Power) — LAN — Power — Hybrid Cable


PSU Output Voltage	Cable Gauge (AWG)	4xaf Output Cable Length	8xaf Output Cable Length	2xbt 90W Output Cable Length	4xbt 90W Output Cable Length
57VDC/750W Power Supply	12	2,400m / 7,874ft	1,040m / 3,412ft	720m / 2,362ft	150m / 492ft
	16	940m / 3,083ft	400m / 1,312ft	240m / 787ft	60m / 196ft

H60 & D60 L2 PRO PoE Switch: Network Topology System

Topology View




Google Map View




Camera Dashboard










D60 Series w/ OS-200 Series IP PoE Back-up Cabinet



PoE (Data + Power) — Power — Fiber

OS-200 Series-System Dash-Board

Power Status

DC Input : 0.0 V
DC Output : 51.40 V
Power Scorce : battery
Output: ON
DC Alarm: N/A

Battery Status

Battery Voltage : 51.42 V
Battery Corruct : 0.9 mA
Capacity : 98%
Time Left (hr) : 11.6
Cycles : 1
Battery Alarm : N/A

Blower / Heater Status

Blower Operation : OFF
Heater Operation : ON

Temp / Humi Status

Temperature : 25°C
Humidity : 51%

GPS Status

Date UTC : 2021/12/20
UTC Time: 07:39:37
Latitude: N 24.99769629953151
Longtitude : E 121.49383638271591
Satellite : 2

OS-200 Series-Notification

Syslog

Email

SNMP

Event

View Log

Ordering information

TX Site - Outdoor

Outdoor IP67/IK10 Gigabit PoE Switches Type



H40-022-90-DC
- 2xGbE PoE (95W) + 2 x GbE SFP
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H40-022-90-DC-A
- 2xGbE PoE (95W) + 2 x GbE SFP
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)
- Support Avigilon Mount



H40-044-30-DC
- 4xGbE PoE (30W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H40-044-91-DC
- 4xGbE bt PoE (90W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H40-082-30-DC
- 8xGbE PoE (30W) +2xGbE SFP
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)

L2 Outdoor IP67/IK10 Gigabit PoE Switches Type



H51-044-30-DC
- 4xGbE PoE (30W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H51-044-91-DC
- 4xGbE bt PoE (90W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H51-084-30-DC
- 8xGbE PoE (30W) + 4xGbE SFP
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)

L2 PRO Outdoor IP67/IK10 Gigabit PoE Switches Type



H60-044-30-DC
- 4xGbE PoE (30W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H60-044-91-DC
- 4xGbE bt PoE (90W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)



H60-084-30-DC
- 8xGbE PoE (30W) + 4xGbE SFP
- 12~56VDC Input
- -40°C~ 65°C (-40°F~ 149°F)

TX Site - Industrial

Industrial Din-Rail Gigabit PoE Switches Type



D40-044-30-DC
- 4xGbE 30W PoE + 2xGbE SFP +2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D40-044-91-DC
- 4x 90W bt PoE + 2xGbE SFP +2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D40-082-30-DC
- 8xGbE 30W PoE +2xGbE SFP
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)

L2 Industrial Din-Rail Gigabit PoE Switches Type



D51-044-30-DC
- 4xGbE PoE (30W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D51-044-91-DC
- 4xGbE bt PoE (90W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D51-084-30-DC
- 8xGbE PoE (30W) + 4xGbE SFP
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)

L2 PRO Industrial Din-Rail Gigabit PoE Switches Type



D60-044-30-DC
- 4xGbE PoE (30W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D60-044-91-DC
- 4xGbE bt PoE (90W) + 2xGbE SFP + 2xGbE RJ45
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)



D60-084-30-DC
- 8xGbE PoE (30W) + 4xGbE SFP
- 12~56VDC Input
- -40°C~75°C (-40°F~167°F)

RX Site

Accessories



CH-200
- 6-CH Power & Fiber Distribution Chassis



HE10-110-RX
- 1-CH EPoH RX Base

EPoC (Ethernet & Power over Coax)

EPoC Power - Distance Chart




PoE (Data + Power)
Coax (Data + Power)

EPoT Power - Distance Chart




PoE (Data + Power)



	100m (328ft)	300m (984ft)	500m (1,640ft)	800m (2,625ft)	1000m (3,281ft)	1200m (3,937ft)
Cat.5e:100m	50.52W	26.4W	17.48W	12.63W	8.84W	8.48W
Cat.5e:1m	57.17W	34.72W	25.2W	13.11W	10W	9.66W
Data Rate	100Mbps	100Mbps	100Mbps	100Mbps	100Mbps	100Mbps

Application



PoE (Data + Power) Coax (Data + Power) Dry contact Power










EPoC (Ethernet & Power over Coax)

EPoC (Ethernet & Power over Coax) Topology


A: 1 - to - 1



PoE (Data + Power)
Coax (Data + Power)

PoE Budget : 9.7W@1,200m / 3,937ft over RG6
Data Rate : 100Mbps


B: 1 - to - 2



PoE (Data + Power)
Coax (Data + Power)

PoE Budget : 25W@500m / 1,640ft over RG6
Data Rate : 100Mbps


C: Daisy - Chain



PoE (Data + Power)
Coax (Data + Power)

PoE Budget : 8W@400m / 1,312ft over RG6
Data Rate : 100Mbps

D: Ring (Failover)



PoE (Data + Power)
Coax (Data + Power)

PoE Budget : 8W@400m / 1,312ft over RG6
Data Rate : 100Mbps

EoC (Ethernet over Coax) Topology


E: 1 - to - 1



Power
Coax (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over RG6
Data Rate : 100Mbps


F: 1 - to - 2



Power
Coax (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over RG6
Data Rate : 100Mbps


G: Daisy - Chain



Power
Coax (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over RG6
Data Rate : 100Mbps

H: Ring (Failover)



Power
Coax (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over RG6
Data Rate : 100Mbps

EPoC RX Switch




XC10-041-250

Features

- 4xBNC coaxial ports, 1xGbE RJ45 LAN port
- 240W power budget for 4 EPoC ports
- 6KV surge protection for EPoC port
- Plug-and-Play deployment PoE IP migration or PoE extension
- Supports 1-to-1, 1-to-2, Daisy-chain, Ring Topologies

Application



Topology	EPoC	EoC
1-to-1	A:	E:
1-to-2	B:	F:
Daisy-Chain	C:	G:
Ring(Failover)	D:	H:




XC10-084-380

Features

- 8xBNC coaxial ports, 2xGbE RJ45 & 2xGbE SFP LAN ports
- 370W power budget for 8 EPoC ports
- 6KV surge protection for EPoC port
- Plug-and-Play deployment PoE IP migration or PoE extension
- Supports 1-to-1, 1-to-2, Daisy-chain, Ring Topologies

Application



Topology	EPoC	EoC
1-to-1	A:	E:
1-to-2	B:	F:
Daisy-Chain	C:	G:
Ring(Failover)	D:	H:

EPoC (Ethernet & Power over Coax)

EPoC RX Adapter




XE10-110-RX

Features

- One BNC coaxial port & one 10/100Mbps LAN port
- PoE pass through coax to remote PoE IP camera
- Including 65W@ 56VDC power adapter
- Supports 1-to-1, 1-to-2, Daisy-chain, Ring Topologies

Applications




Topology	EPoC	EoC
1-to-1	A: ●	E: ●
1-to-2	B: ●	F: ●
Daisy-Chain	C: ●	G: ●
Ring(Failover)	D: ●	H: ●



XE11-110-RX

Features

- One BNC coaxial port & one 10/100Mbps PoE PD port
- 30W/60W/90W PoE input
- Without requiring extra power adapter
- PoE pass through coax to remote PoE IP camera
- Supports 1-to-1, 1-to-2, Daisy-chain, Ring Topologies



Topology	EPoC	EoC
1-to-1	A: ●	E: ●
1-to-2	B: ●	F: ●
Daisy-Chain	C: ●	G: ●
Ring(Failover)	D: ●	H: ●

EPoC TX Adapter



XE10-110-TX

Features

- One BNC coaxial port & one PoE LAN port
- Re-uses existing coax for a PoE IP camera
- Without requiring extra power adapter beside remote PoE IP camera
- PoE Output On/Off control
- Supports 1-to-1, Daisy-chain, Ring Topologies



Topology	EPoC	EoC
1-to-1	A: ●	E: ●
Daisy-Chain	C: ●	G: ●
Ring(Failover)	D: ●	H: ●



XE12-120-TX

Features

- One BNC coaxial port & two PoE LAN ports
- Re-uses existing coax for 2 of PoE IP cameras
- Without requiring extra power adapter beside remote PoE IP cameras
- PoE Output On/Off control
- Supports 1-to-2 Topology



Topology	EPoC	EoC
1-to-2	B: ●	F: ●

IP67/IK10 EPoC TX Adapter



XE22-110-TX

Features

- IP67, IK10, -30°C ~ 60°C
- Built-in 6KV EPoC surge protection
- Re-uses existing coax for a PoE IP camera
- One BNC coaxial port & one PoE LAN port
- PoE Output On/Off control
- Supports 1-to-1, Daisy-chain, Ring Topologies

Applications



Topology	EPoC	EoC
1-to-1	A: ●	E: ●
Daisy-Chain	C: ●	G: ●
Ring(Failover)	D: ●	H: ●



XE22-120-TX

Features

- IP67, IK10, -30°C ~ 60°C
- Built-in 6KV EPoC surge protection
- Re-uses existing coax for 2 of PoE IP cameras
- One BNC coaxial port & two PoE LAN ports
- PoE Output On/Off control
- Supports 1-to-2 Topology



Topology	EPoC	EoC
1-to-2	B: ●	F: ●

EPoC TX Camera Housing




A5000-E

Features

- EPoC-TX Camera Housing
- 20W power budget@600m PoE solution over single coax
- Compatible with IEEE 802.3af IP box/brick camera
- IP68 / IK10 / 6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens

Applications





A5020-E

Features

- EPoC-TX Camera Housing w/IR illuminator(50m)
- 25W power budget@500m PoE solution over single coax
- IP66 / IK10 / 6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens



A5100-E

Features

- EPoC-TX Camera Housing w/germanium window
- 13W power budget@800m PoE solution over single coax
- IP68 / IK10 /6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens

EPoC Related Product



CH-100-V2
- 19'', 1U 4-bay Rack Mount Chassis
- For 4 sets of XE10-110-RX & 65W power adapter



CH-110-V2
- 19'', 1U 8-bay rack mount chassis
- For 8 pieces of XE11-110-RX



SD-301
- BNC Surge Protector
- 6KV Surge Protection



BNC-T
- T-Type BNC Adapter




BNC-YC
- Outdoor Y-Type BNC Cable



BNC-Y
- Y-Type BNC Adapter

EPoT (Ethernet & Power over UTP/STP) Topology


A: 1 - to - 1



PoE (Data + Power)

PoE Budget : 9.7W@1,200m / 3,937ft over Cat6
Data Rate : 100Mbps


B: 1 - to - 2



PoE (Data + Power)

PoE Budget : 25W@500m / 1,640ft over Cat6
Data Rate : 100Mbps


C: Daisy - Chain



PoE (Data + Power)

PoE Budget : 8W@400m / 1,312ft over Cat6
Data Rate : 100Mbps

D: Ring (Failover)



PoE (Data + Power)

PoE Budget : 8W@400m / 1,312ft over Cat6
Data Rate : 100Mbps

EoT (Ethernet over UTP/STP) Topology


E: 1 - to - 1



Power
UTP/STP (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over Cat6
Data Rate : 100Mbps


F: 1 - to - 2



Power
UTP/STP (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over Cat6
Data Rate : 100Mbps


G: Daisy - Chain



Power
UTP/STP (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over Cat6
Data Rate : 100Mbps

H: Ring (Failover)



Power
UTP/STP (Data)
PoE (Data + Power)

Range : 2,400m / 7,874ft over Cat6
Data Rate : 100Mbps

EPoT RX Adapter




TE10-110-RX

Features

- One EPoT RJ45 port & one 10/100Mbps LAN port
- PoE pass through UTP/STP to remote PoE IP camera
- Including 65W@ 56VDC power adapter
- Supports 1-to-1, 1-to-2, Daisy-chain & Ring Topologies

Application



Topology	EPoT	EoT
1-to-1	A:	E:
1-to-2	B:	F:
Daisy-Chain	C:	G:
Ring(Failover)	D:	H:




TE11-110-RX

Features

- One EPoT RJ45 port & one 10/100Mbps PoE PD port
- 30W/60W/90W PoE input
- Without requiring extra power adapter
- PoE pass through UTP/STP to remote PoE IP camera
- Supports 1-to-1, 1-to-2, Daisy-chain, Ring Topologies

Application



Topology	EPoT	EoT
1-to-1	A:	E:
1-to-2	B:	F:
Daisy-Chain	C:	G:
Ring(Failover)	D:	H:

EPoT TX Adapter




TE10-110-TX

Features

- One EPoT RJ45 port & one PoE LAN port
- Without requiring extra power adapter beside remote PoE IP camera
- PoE Output On/Off control
- Supports 1-to-1, Daisy-chain, Ring Topologies

Application



Topology	EPoT	EoT
1-to-1	A:	E:
Daisy-Chain	C:	G:
Ring(Failover)	D:	H:

EPoT (Ethernet & Power over UTP/STP)

EPoT TX Adapter




TE12-120-TX

Features

- One EPoT RJ45 port & two PoE LAN ports
- Without requiring extra power adapter beside remote PoE IP cameras
- PoE Output On/Off control
- Supports 1-to-2 Topology

Application



Topology	EPoT	EoT
1-to-2	B: ●	F: ●

IP67/IK10 EPoT TX Adapter




TE22-110-TX

Features

- IP67, IK10, -30°C ~ 60°C
- Built-in 6KV EPoT surge protection
- One EPoT RJ45 port & one PoE LAN port
- Without requiring extra power adapter beside remote PoE IP camera
- PoE Output On/Off control
- Supports 1-to-1, Daisy-chain, Ring Topologies

Application



Topology	EPoT	EoT
1-to-1	A: ●	E: ●
Daisy-Chain	C: ●	G: ●
Ring(Failover)	D: ●	H: ●



TE22-120-TX

Features

- IP67, IK10, -30°C ~ 60°C
- Built-in 6KV EPoT surge protection
- One EPoT RJ45 port & two PoE LAN ports
- Without requiring extra power adapter beside remote PoE IP cameras
- PoE Output On/Off control
- Supports 1-to-2 Topology

Application



Topology	EPoT	EoT
1-to-2	B: ●	F: ●

EPoT TX Camera Housing



A5000-T

Features

- EPoT-TX Camera Housing
- 20W power budget@600m PoE solution over single UTP/STP
- Compatible with IEEE 802.3af IP box/brick camera
- IP68 / IK10 / 6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens



A5020-T

Features

- EPoT-TX Camera Housing w/IR illuminator(50m)
- 25W power budget@500m PoE solution over single UTP/STP
- IP66 / IK10 / 6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens





A5100-T

Features

- EPoT-TX Camera Housing w/germanium window
- 13W power budget@800m PoE solution over single UTP/STP
- IP68 / IK10 /6KV surge protection
- Window heater & blower included
- Supports wide-angle & long-distance remote focus lens

Applications





EPoT Related Product



CH-100-V2
- 19", 1U 4-bay rack mount chassis
- For 4 sets of TE10-110-RX & 65W power adapter



CH-110-V2
- 19", 1U 8-bay rack mount chassis
- For 8 pieces of TE11-110-RX



UTP-YC cable
- Outdoor Y type RJ45 Cable

EPo2 (Ethernet & Power over 2 Wires) Topology

EPo2 RX Adapter



2E10-110-RX

Features

- One EPo2 terminal block port & one 10/100Mbps LAN port
- Includes 65W@ 56VDC power adapter
- Uses telephone line, doorbell wire or 1-pair UTP/STP to connect EPo2 TX
- Re-uses in-wall 2 wires infrastructure



2E11-110-RX

Features

- One EPo2 Terminal block port & one 10/100Mbps PoE PD port
- 30W/60W/90W PoE input
- Without requiring extra power adapter
- Uses telephone line, doorbell wire or 1-pair UTP/STP to connect EPo2 TX
- Re-uses in-wall 2 wires infrastructure

EPo2 TX Adapter




2E10-110-TX

Features

- One EPo2 Terminal block port & one 10/100Mbps PoE port
- Without requiring extra power adapter beside remote PoE IP device
- Uses telephone line, doorbell wire or 1-pair UTP/STP to connect PoE IP devices
- PoE Output On/Off control

Applications



Power / Distance Table : 2 Wires

Power / Distance Table				
	100m	200m	400m	600m
0.4mm Cable 26AWG	Watt : 18W	Watt : 8.06W	X	X
0.5mm Cable 24AWG	Watt : 23.8W	Watt : 12.1W	Watt : 6.1W	X
0.6mm Cable 22AWG	Watt : 32.3W	Watt : 17.2W	Watt : 8.4W	Watt : 5W
Data Rate	100Mbps	100Mbps	100Mbps	100Mbps

EPo2 Related Product



CH-100-V2

- 19", 1U 4-bay rack mount chassis
- For 4 sets of 2E10-11--RX & 65W power adapter



CH-110-V2

- 19", 1U 8-bay rack mount chassis
- For 8 pieces of 2E11-110-RX

PoE Extender Topology

Indoor / Outdoor IP67/IK10 Gigabit 90W bt PoE++ Extender



E59-101



E69-101

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 1-port Gigabit Passive PoE output (Compliant 802.3af)
- Drives the reach beyond restricted 100m Ethernet distance



E59-102



E69-102

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 2-port Gigabit Passive PoE output (Compliant 802.3af)
- Drives the reach beyond restricted 100m Ethernet distance

Outdoor IP67/IK10 IEEE 802.3bt PoE++ to IEEE 802.3af/at/bt PoE++ Extender



E69-201

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 1-port Gigabit **802.3af/at/bt PoE++ output**
- IEEE 802.3af/at/bt compliant
- Drives the reach beyond restricted 100m Ethernet distance



E69-202

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 2-port Gigabit **802.3af/at/bt PoE++ output**
- IEEE 802.3af/at/bt compliant
- Drives the reach beyond restricted 100m Ethernet distance

Indoor / Outdoor IP67/IK10 Gigabit 90W PoE Extender Plus



E59-602




E69-602

Features

- Voltage Booster
- 1-port Gigabit **30W/60W/90W bt PoE input** + 1-port Gigabit 56VDC Passive PoE output + (Compliant 802.3af)
  1-port Gigabit **24VDC or 56VDC** Passive PoE output
- Drives the reach beyond restricted 100m Ethernet distance

Application



PoE Switch Product Guide

Outdoor IP67/IK10 PoE Switch

Indoor PoE Switch

Industrial PoE Switch





Outdoor / Indoor PoE Switch Product Selection

30W at PoE | 60W/90W bt PoE | 60W/95W PoH PoE

Outdoor
IP67 / IK10

Fast Ethernet
- 5-port
  - H21-041-30-075 P17
- 10-port
  - H21-082-31-150 P17

Gigabit Ethernet
- 4-port
  - H40-022-91-120 P17
  - H40-022-90-120 P17
  - H40-022-90-DC P18
  - H40-022-91-DC P18
  - H40-022-90-120-A P17
- 8-port
  - H40-044-30-150 P17
  - H40-044-91-250 P17
  - H40-044-90-250 P17
  - H40-044-30-DC P18
  - H40-044-91-DC P18
  - H40-044-90-DC P18
- 10-port
  - H40-082-30-250 P17
  - H40-082-30-DC P18

-DC:12~56VDC Input Power
Others:100~240VAC Input Power



24VDC PoE | 30W at PoE

Outdoor
IP67 / IK10

Gigabit Ethernet
- 6-port
  - H42-042-30-075 P18



30W at PoE

Indoor

Fast Ethernet
- 6-port
  - C11-042-30-065 P19
- 10-port
  - C11-082-32-120 P19
- 18-port
  - C11-162-31-250 P19
- 26-port
  - C11-242-31-380 P19



Industrial PoE Switch Product Selection

30W at PoE | 60W/90W bt PoE | 60W/95W PoH PoE

Industrial -40~75°C — Gigabit Ethernet

- 6-port
  - H30-042-30 P19
  - H36-042-30 P20
- 8-port
  - H30-044-30 P19
  - D40-044-30 P20
  - D40-044-91 P20
  - D40-044-91-DC P21
  - H30-044-90 P19
  - D40-044-30-DC P21
  - H30-044-91 P19
  - H36-044-91 P20
  - H36-044-90 P20
- 10-port
  - D40-082-30 P20
  - D40-082-30-DC P21
  - H30-082-30 P19
  - H36-082-30 P20

-DC:12~56VDC Input Power

Others:48~56VDC Input Power

24VDC PoE

30W at PoE

Industrial -40~75°C — Gigabit Ethernet

- 6-port
  - H32-042-30 P20





Outdoor IP67/IK10 PoE Switch

Outdoor IP67/IK10

H21 Series - Outdoor IP67/IK10 Fast Ethernet EXPoE Switch



H21-041-30-075

Features

- IP67, IK10, -40°C ~ 65°C
- 4-port 10/100Mbps 30W PoE + 1-port 10/100Mbps
- 12KV PoE surge protection
- **EX mode "on" reaches 802.3af camera up to 250m@10Mbps**
- 100~240VAC input power




H21-082-31-150

Features

- **Outdoor IP67, IK10, -20°C ~ 65°C**
- 8-port 10/100Mbps 30W PoE + 2-port Gigabit Combo(RJ45/SFP)
- 6KV PoE surge protection
- **EX mode "on" reaches 802.3af camera up to 250m@10Mbps**
- 100~240VAC input power

Application



PoE (Data + Power) — Ethernet (Data) — Power — Fiber

H40 Series - Outdoor IP67/IK10 Gigabit Ethernet PoE Switch



H40-022-90-120

Features

- IP67, IK10, -40°C~ 65°C
- **30W at, 60W/95W PoH PoE output**
- 2-port Gigabit 95W PoH PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H40-022-90-120-A

Features

- IP67, IK10, -40°C~ 65°C
- **30W at, 60W/95W PoH PoE output**
- 2-port Gigabit 95W PoH PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- For Avigilon PTZ/IR PTZ/Multisensor
- 100~240VAC input power



H40-022-91-120

Features

- IP67, IK10, -40°C~ 65°C
- **30W at, 60W/90W bt PoE output**
- 2-port Gigabit 90W bt PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H40-044-30-150

Features

- IP67, IK10, -40°C~ 65°C
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H40-044-90-250

Features

- IP67, IK10, -40°C~ 65°C
- **30W at, 60W/95W PoH PoE output**
- 4-port Gigabit 95W PoH PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H40-044-91-250

Features

- IP67, IK10, -40°C~ 65°C
- **30W at, 60W/90W bt PoE output**
- 4-port Gigabit 90W bt PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power





H40-082-30-250


Features

- IP67, IK10, -40°C~ 65°C
- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power

Applications







PoE (Data + Power) — Power — Fiber

Outdoor IP67 / IK10 PoE Switch

H42 Series - Outdoor IP67/IK10 Gigabit Ethernet Switch w/ Adjustable PoE Output




H42-042-30-075

Features

- IP67, IK10, -40°C~ 65°C
- 4-port Gigabit 30W PoE + **1-port Gigabit (24VDC/56VDC) Passive PoE** + 1-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power

Application



H40-DC Series - Outdoor IP67/IK10 Gigabit Ethernet PoE Switch w/ 12~56VDC Input



H40-022-90-DC

Features

- IP67, IK10, -40°C~ 65°C
- 30W at, 60W/95W PoH PoE output
- 2-port Gigabit 95W PoH PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H40-022-91-DC

Features

- IP67, IK10, -40°C~ 65°C
- 30W at, 60W/90W bt PoE output
- 2-port Gigabit 90W bt PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H40-044-30-DC

Features

- IP67, IK10, -40°C~ 65°C
- 4-port Gigabit 30W PoE + 2-port Gigabit SFP + 2-port Gigabit RJ45
- 6KV PoE surge protection
- 12~56VDC input power



H40-044-90-DC

Features

- IP67, IK10, -40°C~ 65°C
- 30W at, 60W/95W PoH PoE output
- 4-port Gigabit 90W bt PoE + 2-port Gigabit SFP + 2-port Gigabit RJ45
- 6KV PoE surge protection
- 12~56VDC input power



H40-044-91-DC

Features

- IP67, IK10, -40°C~ 65°C
- 30W at, 60W/90W bt PoE output
- 4-port Gigabit 90W bt PoE + 2-port Gigabit SFP + 2-port Gigabit RJ45
- 6KV PoE surge protection
- 12~56VDC input power





H40-082-30-DC


Features

- IP67, IK10, -40°C~ 65°C
- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power

Applications







PoE (Data + Power) Power Fiber Ethernet (Data) Hybrid Cable







Indoor / Industrial PoE Switch

Indoor

C11 Series - EXPoE Switch



C11-042-30-065

Features

- 4-port 10/100Mbps 30W PoE + 2-port 10/100Mbps
- IEEE 802.3at compliant
- 4KV PoE surge protection
- EX mode “on” reaches 802.3af camera up to 250m@10Mbps
- 100~240VAC input power



C11-082-32-120

Features

- 8-port 10/100Mbps 30W PoE + 2-port Gigabit Combo (RJ45/SFP)
- IEEE 802.3at compliant
- 6KV PoE surge protection
- EX mode “on” reaches 802.3af camera up to 250m@10Mbps
- 100~240VAC input power



C11-162-31-250

Features

- 16-port 10/100Mbps 30W PoE + 2-port Gigabit Combo (RJ45/SFP)
- IEEE 802.3at compliant
- 6KV PoE surge protection
- EX mode “on” reaches 802.3af camera up to 250m@10Mbps
- 100~240VAC input power




C11-242-31-380

Features

- 24-port 10/100Mbps 30W PoE + 2-port Gigabit Combo (RJ45/SFP)
- IEEE 802.3at compliant
- 6KV PoE surge protection
- EX mode “on” reaches 802.3af camera up to 250m@10Mbps
- 100~240VAC input power

Applications



Industrial

H30 Series - Industrial Gigabit Ethernet PoE Switch w/ Adjustable PoE Output



H30-042-30

Features

- 4-port Gigabit 30W PoE + 1-port Gigabit RJ45 + 1-port Gigabit SFP
- 6KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power



H30-044-30

Features

- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 12KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power



H30-044-90

Features

- 30W at, 60W/95W PoH PoE output
- 4-port Gigabit 95W PoH PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 12KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



H30-044-91

Features

- 30W at, 60W/90W bt PoE output
- 4-port Gigabit 90W bt PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 12KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power





H30-082-30


Features

- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- 12KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power

Applications







H32 Series - Industrial Gigabit Ethernet PoE Switch w/ Adjustable PoE Output




H32-042-30

Features

- 4-port Gigabit 30W PoE + **1-port Gigabit (24VDC/56VDC) PoE** + 1-port Gigabit SFP
- 6KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power

Application



H36 Series - Industrial Gigabit Ethernet PoE Switch w/ 12V~56VDC Input



H36-042-30

Features

- 4-port Gigabit 30W PoE + 1-port Gigabit RJ45 + 1-port Gigabit SFP
- **12V~56VDC Input Power**
- 6KV PoE surge protection
- -40°C~75°C operating temperature
- 12~56VDC input power



H36-044-90

Features

- **30W/60W/95W PoH PoE output**
- 4-port Gigabit 95W PoH PoE +2-port Gigabit RJ45 + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 12KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



H36-044-91

Features

- **30W/60W/90W bt PoE output**
- 4-port Gigabit 90W bt PoE +2-port Gigabit RJ45 + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 12KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power




H36-082-30

Features

- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 12KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power

Applications



D40 Series - Industrial Gigabit Ethernet PoE Switch



D40-044-30

Features

- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power



D40-044-91

Features

- **30W/60W/90W bt PoE output**
- 4-port Gigabit 90W bt PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power




D40-082-30

Features

- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- 6KV PoE surge protection
- IEEE 802.3at compliant
- -40°C~75°C operating temperature
- 48~56VDC input power

Applications



Indoor / Industrial PoE Switch

D40-DC Series - Industrial Din-Rail Type Powered by 12-56VDC



D40-044-30-DC

Features

- 4-port Gigabit 30W PoE +2-port Gigabit RJ45 + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D40-044-91-DC

Features

- **30W at, 60W/90W bt PoE output**
- 4-port Gigabit 90W bt PoE +2-port Gigabit RJ45 + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power




D40-082-30-DC

Features

- 8-port Gigabit 30W PoE + 2-port Gigabit SFP
- **12V~56VDC Input Power**
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power

Applications



Related Products

SFP Transceiver



SFP-SX-X5
1.25G Multi-Mode SFP
850nm, 0.5KM, 0°C~70°C



SFP-SX-02
1.25G Multi-Mode SFP, LC
1310nm, 2KM, 0°C ~ 70°C



SFP-LX-10
1.25G Single-Mode SFP, LC
1310nm, 10KM, 0°C ~ 70°C



SFP-LX-40
1.25G Single-Mode SFP, LC
1310nm, 40KM, 0°C ~ 70°C



SFP-LX-80
1.25G Single-Mode SFP, LC
1310nm, 80KM, 0°C ~ 70°C



SFP-TX-X1
1000BaseT, SFP to RJ45
100M, 0°C ~ 70°C

Industrial SFP Transceiver



SFP-ISX-X5
1.25G Multi-Mode SFP
850nm, 0.5KM, -40°C ~ 85°C



SFP-ISX-02
1.25G Multi-Mode SFP, LC
1310nm, 2KM, -40°C ~ 85°C



SFP-ILX-10
1.25G Single-Mode SFP, LC
1310nm, 10KM, -40°C ~ 85°C



SFP-ILX-40
1.25G Single-Mode SFP, LC
1310nm, 40KM, -40°C ~ 85°C



SFP-ILX-80
1.25G Single-Mode SFP, LC
1310nm, 80KM, -40°C ~ 85°C



SFP-ITX-X1
1000BaseT, SFP to RJ45
100M, -40°C ~ 85°C

SFP+ Transceiver



SFPP-SR-X3
10G Multi-Mode SFP+LC
850nm, 0.3KM, 0°C ~ 70°C



SFPP-LR-10
10G Single-Mode SFP+LC
1310nm, 10KM, 0°C ~ 70°C



SFPP-ER-40
10G Single-Mode SFP+LC
1310nm, 40KM, 0°C ~ 70°C



SFPP-ZR-80
10G Single-Mode SFP+LC
1310nm, 80KM, 0°C ~ 70°C



SFPP-TX-X03
10G, SFP+ to RJ45, 30M
0°C ~ 70°C

Industrial SFP+ Transceiver



SFPP-ISR-X3
IND 10G SFP+, MMF,
850NM, 300M



SFPP-ILR-10
IND 10G SFP+, SMF,
1310NM, 10KM



SFPP-IER-40
IND 10G SFP+, SMF,
1550NM, 40KM

BiDi SFP Transceiver



SFP-ALX-02
1.25G SFP,MMF Bi-Di,
TX:1310NM / RX:1550NM,2KM



SFP-BLX-02
1.25G SFP,MMF Bi-Di,
TX:1550NM / RX:1310NM,2KM

BiDi SFP Transceiver



SFP-ALX-20
1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-BLX-20
1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM



SFP-ALX-40
1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-BLX-40
1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM

Industrial BiDi SFP Transceiver



SFP-IALX-02
IND 1.25G SFP,MMF Bi-Di,
TX:1310NM / RX:1550NM,2KM

Related Products

Industrial BiDi SFP Transceiver



SFP-IBLX-02
IND 1.25G SFP,MMF Bi-Di,
TX:1550NM / RX:1310NM,2KM



SFP-IALX-20
IND 1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-IBLX-20
IND 1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM



SFP-IALX-40
IND 1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,40KM



SFP-IBLX-40
IND 1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,40KM

BiDi SFP+ Transceiver



SFPP-ALR-02
10G SFP,MMF Bi-Di,
TX:1270NM / RX:1330NM,2KM



SFPP-BLR-02
10G SFP,MMF Bi-Di,
TX:1330NM / RX:1270NM,2KM



SFPP-ALR-20
10G SFP,SMF Bi-Di,
TX:1270NM / RX:1330NM,20KM



SFPP-BLR-20
10G SFP,SMF Bi-Di,
TX:1330NM / RX:1270NM,20KM



SFPP-ALR-40
10G SFP,SMF Bi-Di,
TX:1270NM / RX:1330NM,40KM

BiDi SFP+ Transceiver



SFPP-BLR-40
10G SFP,SMF Bi-Di,
TX:1330NM / RX:1270NM,40KM

Pole Mount



AT-100
Pole Mount Adapter

Corner Mount



AT-101
Pole Mount Adapter



AT-200
Corner Mount Adapter

Junction Box



JB-200
Junction Box

Industrial Power Supply



NDR-75-48
Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W
-20°C ~ 70°C



NDR-120-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/120W
-20°C ~ 70°C



NDR-240-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/240W
-20°C ~ 70°C



NDR-480-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/480W
-20°C ~ 70°C



MDR-10-12
Indoor Industrial Din-Rail Power Supply, 12 V AC/DC/10W
-20°C ~ 70°C

Industrial Power Supply



MDR-40-48
Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W
-20°C ~ 70°C



HLG-120H-54
Outdoor Industrial Power Supply
54VDC/120W
-40°C ~ 70°C, IP67



HLG-240H-54
Outdoor Industrial Power Supply
54VDC/240W
-40°C ~ 70°C, IP67



DRL-48V120W1EN
Indoor Industrial Din-Rail Power Supply
48V, 120W



DRL-48V240W1EN
Indoor Industrial Din-Rail Power Supply
48V, 240W

Fiber Splice Tray



AT-300
Fiber Splice Tray
For H40-044/082 Series
&H21-082 use.



AT-301
Fiber Splice Tray
For H80 Series use.



AT-302
Fiber Splice Tray
For H40/H42/H40-A Series use.



AT-303
Fiber Splice Tray
For H40-V3/H60 Series use.

Side opening alarm switch kit



BK-402
Side opening alarm switch kit
For H40 Series & H60 Series use.



BK-403
Side opening alarm switch kit
For H80-044-30-150
H80-084-30-250 use.



BK-404
Side opening alarm switch kit
For H40/H42/H40-A Series use.

L2 PRO PoE Switch Product Guide

L2 PoE Switch

- Outdoor IP67/IK10
- Industrial
- Indoor

10G L2 PRO Switch

- Indoor

L2 PRO PoE Switch

- Outdoor IP67/IK10
- Industrial
- Indoor



Outdoor / Industrial / Indoor L2 & L2 PRO Gigabit Ethernet PoE Switch

Outdoor PoE Switch
IP67 / IK10 — Gigabit Ethernet

-DC:12~56VDC Input Power
Others:100~240VAC Input Power

	30W at PoE	60W/90W bt/PoH PoE	60W/90W bt PoE
8-port	H51-044-30-150 P27, H51-044-30-DC P28, H60-044-30-150 P29, H60-044-30-DC P30	H51-044-90-250 P27, H51-044-90-DC P28, H60-044-90-250 P30, H60-044-90-DC P30	H51-044-91-250 P27, H51-044-91-DC P28, H60-044-91-250 P30, H60-044-91-DC P30
12-port	H51-084-30-250 P27, H51-084-30-DC P28, H60-084-30-250 P30, H60-084-30-DC P30		

Industrial
-40~75°C — Gigabit Ethernet


-DC:12~56VDC Input Power
Others:48~56VDC Input Power

8-port	D51-044-30 P27, D51-044-30-DC P28, D51-044-91 P27, D51-044-91-DC P28, D51-044-90 P27, D51-044-90-DC P28, D60-044-30 P29, D60-044-30-DC P30, D60-044-91 P29, D60-044-91-DC P30, D60-044-90 P29, D60-044-90-DC P30
12-port	D51-084-30 P27, D51-084-30-DC P28, D60-084-30 P29, D60-084-30-DC P30

Indoor
Gigabit Ethernet


	Non - PoE	30W at PoE
10-port		C51-082-30-130 P27, C60-082-30-130 P29
12-port	C60-00B-01 P29	
20-port		C51-164-30-250 P27, C60-164-30-250 P29
28-port	C60-00F-01 P29	C51-244-30-370 P27, C60-244-30-370 P29


Network Topology System



Camera Dashboard









Floor Map View



Google Map View



L2 PRO Gigabit PoE Switch Dashboard



Device List

Show 10 entries Search:

Status	Device Type	Model Name	Device Name	MAC	IP Address
Online	PoESW	H60-084-30-250	H60-8p @ 203 name	68:8D:B6:00:CB:00	192.168.10.203
Online	PoESW	H60-084-30-250	H60-8p @ 209 name	68:8D:B6:00:D1:00	192.168.10.209
Online	IPMX	M6000-AIW	M6000-AIW	68:8D:B6:01:E1:B1	192.168.10.165
Online	IP Camera	SNC-VB635	Sony	D8:D4:3C:DD:F5:C7	192.168.10.122
Online	IP Camera	WV-S1131	Panasonic_WV-S1131	BC:C3:42:71:79:D0	192.168.10.104
Online	IPSG	SD-504	SD-504	68:8D:B6:00:00:01	192.168.10.108
Online	PC	General Computer	FC2564	00:50:56:2D:FA:AC	192.168.10.201
Online	Others	Unknown model	Unknown name	04:D4:C4:2C:B5:EC	192.168.10.1
Online	Others	Unknown model	Unknown name	94:C6:91:5F:9E:EA	192.168.10.180
Online	PC	General Computer	MIS-TEMP-NB4	A0:A8:CD:26:FE:FD	192.168.10.192

Showing 1 to 10 of 29 entries Previous 1 2 3 Next

Edit

Outdoor / Industrial L2 & L2 PRO Gigabit Ethernet PoE Switch

C51 Series - Indoor L2 Gigabit Ethernet PoE Switch w/o Network Topology System



C51-082-30-130

Features

- **8-port Gigabit 30W PoE + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power



C51-164-30-250

Features

- **16-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power




C51-244-30-370

Features

- **24-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power

Application



PoE (Data + Power) — Ethernet (Data) — Fiber

D51 Series - Din-Rail Industrial L2 Gigabit Ethernet PoE Switch w/o Network Topology System



D51-044-30

Features

- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



D51-044-90

Features

- **4-port Gigabit 90W bt / PoH PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



D51-044-91

Features

- **4-port Gigabit 90W bt PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power




D51-084-30

Features

- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power

Application



PoE (Data + Power) — Ethernet (Data) — Fiber

H51 Series - Outdoor IP67/IK10 L2 Gigabit Ethernet PoE Switch w/o Network Topology System



H51-044-30-150

Features

- **IP67, IK10, -40°C~ 65°C**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H51-044-90-250

Features

- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt / PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H51-044-91-250

Features

- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power




H51-084-30-250

Features

- **IP67, IK10, -40°C~ 65°C**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power

Application



PoE (Data + Power) — Power — Fiber

Outdoor / Industrial L2 & L2 PRO Gigabit Ethernet PoE Switch

D51 Series - Din-Rail Industrial L2 Gigabit Ethernet PoE Switch by 12-56VDC w/o Network Topology System



D51-044-30-DC

Features
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D51-044-90-DC

Features
- **4-port Gigabit 90W bt / PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D51-044-91-DC


Features
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D51-084-30-DC

Features
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power

Application



PoE (Data + Power) — Ethernet (Data) — Power — Hybrid Cable

H51 Series - Outdoor IP67/IK10 L2 Gigabit Ethernet PoE Switch by 12-56VDC w/o Network Topology System



H51-044-30-DC

Features
- **IP67, IK10, -40°C~ 65°C**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H51-044-90-DC

Features
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt / PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H51-044-91-DC


Features
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H51-084-30-DC


Features
- **IP67, IK10, -40°C~ 65°C**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power

Application



PoE (Data + Power) — Power — Fiber — Hybrid Cable

Mobile Surveillance Trailer



Outdoor / Industrial L2 PRO Gigabit Ethernet PoE Switch

C60 Series - Indoor L2 PRO 10G Ethernet Switch



C60-00B-01

Features

- **Full 10G Solution**
- Indoor 12x1G/10G SFP+
- 100-240VAC
- 0°C ~ 50°C (32°F ~ 122°F)
- 100~240VAC input power



C60-00F-01

Features

- Indoor 24-port Gigabit RJ45 + 4x1G/10G SFP+
- 100-240VAC
- 0°C ~ 50°C (32°F ~ 122°F
- 100~240VAC input power)

C60 Series - Indoor L2 PRO Gigabit Ethernet PoE Switch



C60-082-30-130

Features

- **Supports NTS**
- **8-port Gigabit 30W PoE + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power



C60-164-30-250

Features

- **Supports NTS**
- **16-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power



C60-244-30-370

Features

- **Supports NTS**
- **24-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP**
- 6KV PoE surge protection
- IEEE 802.3at compliant
- 100~240VAC input power

D60 Series - Din-Rail Industrial L2 PRO Gigabit Ethernet PoE Switch



D60-044-30

Features

- **Supports NTS**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



D60-044-90

Features

- **Supports NTS**
- **4-port Gigabit 90W bt/PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



D60-044-91

Features

- **Supports NTS**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



D60-084-30

Features

- **Supports NTS**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power

H60 Series - Outdoor IP67/IK10 L2 PRO Gigabit Ethernet PoE Switch




H60-044-30-150

Features

- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power

Application







Outdoor / Industrial L2 PRO Gigabit Ethernet PoE Switch

H60 Series - Outdoor IP67/IK10 L2 PRO Gigabit Ethernet PoE Switch



H60-044-90-250

Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt/PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H60-044-91-250


Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power



H60-084-30-250

Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- 100~240VAC input power

Application



PoE (Data + Power) — Power — Fiber

D60-DC Series - Din-Rail Industrial L2 PRO Gigabit Ethernet PoE Switch Powered by 12-56VDC



D60-044-30-DC

Features
- **Supports NTS**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D60-044-90-DC

Features
- **Supports NTS**
- **4-port Gigabit 90W bt/PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D60-044-91-DC


Features
- **Supports NTS**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power



D60-084-30-DC

Features
- **Supports NTS**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power

Application



PoE (Data + Power) — Power — Ethernet (Data) — Hybrid Cable

H60-DC Series - Outdoor IP67/IK10 L2 PRO Gigabit Ethernet PoE Switch Powered by 12-56VDC



H60-044-30-DC

Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- 4-port Gigabit 30W PoE + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H60-044-90-DC

Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt/PoH PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power



H60-044-91-DC


Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- **4-port Gigabit 90W bt PoE** + 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power




H60-084-30-DC

Features
- **Supports NTS**
- **IP67, IK10, -40°C~ 65°C**
- 8-port Gigabit 30W PoE + 4-port Gigabit SFP
- 6KV PoE surge protection
- 12~56VDC input power

Applications



PoE (Data + Power) — Power



PoE (Data + Power) — Power — Ethernet (Data) — Hybrid Cable

Related Products

SFP Transceiver



SFP-SX-X5
1.25G Multi-Mode SFP
850nm, 0.5KM, 0°C~70°C



SFP-SX-02
1.25G Multi-Mode SFP, LC
1310nm, 2KM, 0°C ~ 70°C



SFP-LX-10
1.25G Single-Mode SFP, LC
1310nm, 10KM, 0°C ~ 70°C



SFP-LX-40
1.25G Single-Mode SFP, LC
1310nm, 40KM, 0°C ~ 70°C



SFP-LX-80
1.25G Single-Mode SFP, LC
1310nm, 80KM, 0°C ~ 70°C



SFP-TX-X1
1000BaseT, SFP to RJ45
100M, 0°C ~ 70°C

Industrial SFP Transceiver



SFP-ISX-X5
1.25G Multi-Mode SFP
850nm, 0.5KM, -40°C ~ 85°C



SFP-ISX-02
1.25G Multi-Mode SFP, LC
1310nm, 2KM, -40°C ~ 85°C



SFP-ILX-10
1.25G Single-Mode SFP, LC
1310nm, 10KM, -40°C ~ 85°C



SFP-ILX-40
1.25G Single-Mode SFP, LC
1310nm, 40KM, -40°C ~ 85°C



SFP-ILX-80
1.25G Single-Mode SFP, LC
1310nm, 80KM, -40°C ~ 85°C



SFP-ITX-X1
1000BaseT, SFP to RJ45
100M, -40°C ~ 85°C

SFP+ Transceiver



SFPP-SR-X3
10G Multi-Mode SFP+LC
850nm, 0.3KM, 0°C ~ 70°C



SFPP-LR-10
10G Single-Mode SFP+LC
1310nm, 10KM, 0°C ~ 70°C



SFPP-ER-40
10G Single-Mode SFP+LC
1310nm, 40KM, 0°C ~ 70°C



SFPP-ZR-80
10G Single-Mode SFP+LC
1310nm, 80KM, 0°C ~ 70°C



SFPP-TX-X03
10G, SFP+ to RJ45, 30M
0°C ~ 70°C

Industrial SFP+ Transceiver



SFPP-ISR-X3
IND 10G SFP+, MMF,
850NM, 300M



SFPP-ILR-10
IND 10G SFP+, SMF,
1310NM, 10KM



SFPP-IER-40
IND 10G SFP+, SMF,
1550NM, 40KM

BiDi SFP Transceiver



SFP-ALX-02
1.25G SFP,MMF Bi-Di,
TX:1310NM / RX:1550NM,2KM



SFP-BLX-02
1.25G SFP,MMF Bi-Di,
TX:1550NM / RX:1310NM,2KM

BiDi SFP Transceiver



SFP-ALX-20
1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-BLX-20
1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM



SFP-ALX-40
1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-BLX-40
1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM

Industrial BiDi SFP Transceiver



SFP-IALX-02
IND 1.25G SFP,MMF Bi-Di,
TX:1310NM / RX:1550NM,2KM

Industrial BiDi SFP Transceiver



SFP-IBLX-02
IND 1.25G SFP,MMF Bi-Di,
TX:1550NM / RX:1310NM,2KM



SFP-IALX-20
IND 1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,20KM



SFP-IBLX-20
IND 1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,20KM



SFP-IALX-40
IND 1.25G SFP,SMF Bi-Di,
TX:1310NM / RX:1550NM,40KM



SFP-IBLX-40
IND 1.25G SFP,SMF Bi-Di,
TX:1550NM / RX:1310NM,40KM

BiDi SFP+ Transceiver



SFPP-ALR-02
10G SFP,MMF Bi-Di,
TX:1270NM / RX:1330NM,2KM



SFPP-BLR-02
10G SFP,MMF Bi-Di,
TX:1330NM / RX:1270NM,2KM



SFPP-ALR-20
10G SFP,SMF Bi-Di,
TX:1270NM / RX:1330NM,20KM



SFPP-BLR-20
10G SFP,SMF Bi-Di,
TX:1330NM / RX:1270NM,20KM



SFPP-ALR-40
10G SFP,SMF Bi-Di,
TX:1270NM / RX:1330NM,40KM

BiDi SFP+ Transceiver



SFPP-BLR-40
10G SFP,SMF Bi-Di,
TX:1330NM / RX:1270NM,40KM

Pole Mount



AT-100
Pole Mount Adapter

Corner Mount



AT-101
Pole Mount Adapter

AT-200
Corner Mount Adapter

Junction Box

JB-200
Junction Box

Industrial Power Supply

NDR-75-48
Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W
-20°C ~ 70°C

NDR-120-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/120W
-20°C ~ 70°C

NDR-240-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/240W
-20°C ~ 70°C

NDR-480-48
Indoor Industrial Din-Rail Power Supply, 48~55VDC/480W
-20°C ~ 70°C

MDR-10-12
Indoor Industrial Din-Rail Power Supply, 12 V AC/DC/10W
-20°C ~ 70°C

Related Products

Industrial Power Supply



MDR-40-48
Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W
-20°C ~ 70°C



HLG-120H-54
Outdoor Industrial Power Supply
54VDC/120W
-40°C ~ 70°C, IP67



HLG-240H-54
Outdoor Industrial Power Supply
54VDC/240W
-40°C ~ 70°C, IP67



DRL-48V120W1EN
Indoor Industrial Din-Rail Power Supply
48V, 120W



DRL-48V240W1EN
Indoor Industrial Din-Rail Power Supply
48V, 240W

Fiber Splice Tray



AT-300
Fiber Splice Tray
For H40-044/082 Series
&H21-082 use.



AT-301
Fiber Splice Tray
For H80 Series use.



AT-302
Fiber Splice Tray
For H40/H42/H40-A Series use.



AT-303
Fiber Splice Tray
For H40-V3/H60 Series use.

Side opening alarm switch kit




BK-402
Side opening alarm switch kit
For H40 Series & H60 Series use.




BK-403
Side opening alarm switch kit
For H80-044-30-150
H80-084-30-250 use.



BK-404
Side opening alarm switch kit
For H40/H42/H40-A Series use.







PoE Media Converter
Product Guide

Media Converter
PoE Media Converter
PoE PD Media Converter





Industrial Gigabit PoE Media Converter

Non - PoE | PoE PD | 30W at PoE | 90W bt PoE | 95W PoH PoE



M30 Series - Industrial Gigabit Media Converter



M30-011-01


Features
- 1-port Gigabit RJ45 + 1-port Gigabit SFP
- Support LFP(Link Fault Passthrough)
- 6KV surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC or 24VAC Input Power



M30-022-01

Features
- 2-port Gigabit RJ45 + 2-port Gigabit SFP
- 6KV surge protection
- -40°C ~ 75°C operating temperature
- 12~56VDC input power

Applications



M30 Series - Industrial Gigabit PoE Media Converter



M30-011-30

Features
- 1-port Gigabit 30W PoE + 1-port Gigabit SFP
- Supports LFP(Link Fault Passthrough)
- 6KV surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power



M30-022-90


Features
- 2-port Gigabit 95W PoH PoE + 2-port Gigabit SFP
- 6KV surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power




M30-022-91

Features
- 2-port Gigabit 90W bt PoE + 2-port Gigabit SFP
- 6KV surge protection
- -40°C ~ 75°C operating temperature
- 48~56VDC input power

PoE (Data + Power) | Ethernet (Data) | Fiber | Power





M31 Series - Industrial Gigabit PoE PD Media Converter



M31-011-01

Features
- 1-port Gigabit 30W PoE PD + 1-port Gigabit SFP
- Flexible SFP transceiver port for uplink
- Supporting 10/100/1000Mbps data rates
- -40°C ~ 75°C operating temperature
- 30W PoE or 12VDC Input Power

PoE (Data + Power) | Ethernet (Data) | Fiber | Power

Related Products

SFP Transceiver

					
SFP-SX-X5 1.25G Multi-Mode SFP 850nm, 0.5KM, 0°C~70°C	SFP-SX-02 1.25G Multi-Mode SFP, LC 1310nm, 2KM, 0°C ~ 70°C	SFP-LX-10 1.25G Single-Mode SFP, LC 1310nm, 10KM, 0°C ~ 70°C	SFP-LX-40 1.25G Single-Mode SFP, LC 1310nm, 40KM, 0°C ~ 70°C	SFP-LX-80 1.25G Single-Mode SFP, LC 1310nm, 80KM, 0°C ~ 70°C	SFP-TX-X1 1000BaseT, SFP to RJ45 100M, 0°C ~ 70°C

Industrial SFP Transceiver

					
SFP-ISX-X5 1.25G Multi-Mode SFP 850nm, 0.5KM, -40°C ~ 85°C	SFP-ISX-02 1.25G Multi-Mode SFP, LC 1310nm, 2KM, -40°C ~ 85°C	SFP-ILX-10 1.25G Single-Mode SFP, LC 1310nm, 10KM, -40°C ~ 85°C	SFP-ILX-40 1.25G Single-Mode SFP, LC 1310nm, 40KM, -40°C ~ 85°C	SFP-ILX-80 1.25G Single-Mode SFP, LC 1310nm, 80KM, -40°C ~ 85°C	SFP-ITX-X1 1000BaseT, SFP to RJ45 100M, -40°C ~ 85°C

BiDi SFP Transceiver

				
SFP-ALX-02 1.25G SFP,MMF Bi-Di, TX:1310NM / RX:1550NM,2KM	SFP-BLX-02 1.25G SFP,MMF Bi-Di, TX:1550NM / RX:1310NM,2KM	SFP-ALX-20 1.25G SFP,SMF Bi-Di, TX:1310NM / RX:1550NM,20KM	SFP-BLX-20 1.25G SFP,SMF Bi-Di, TX:1550NM / RX:1310NM,20KM	SFP-ALX-40 1.25G SFP,SMF Bi-Di, TX:1310NM / RX:1550NM,20KM

BiDi SFP Transceiver

Industrial BiDi SFP Transceiver

				
SFP-BLX-40 1.25G SFP,SMF Bi-Di, TX:1550NM / RX:1310NM,20KM	SFP-IALX-02 IND 1.25G SFP,MMF Bi-Di, TX:1310NM / RX:1550NM,2KM	SFP-IBLX-02 IND 1.25G SFP,MMF Bi-Di, TX:1550NM / RX:1310NM,2KM	SFP-IALX-20 IND 1.25G SFP,SMF Bi-Di, TX:1310NM / RX:1550NM,20KM	SFP-IBLX-20 IND 1.25G SFP,SMF Bi-Di, TX:1550NM / RX:1310NM,20KM

Industrial BiDi SFP Transceiver

Industrial Power Supply

				
SFP-IALX-40 IND 1.25G SFP,SMF Bi-Di, TX:1310NM / RX:1550NM,40KM	SFP-IBLX-40 IND 1.25G SFP,SMF Bi-Di, TX:1550NM / RX:1310NM,40KM	SFP-IBLX-40 IND 1.25G SFP,SMF Bi-Di, TX:1550NM / RX:1310NM,40KM	NDR-75-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/75W -20°C ~ 70°C	NDR-120-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/120W -20°C ~ 70°C

Industrial Power Supply

Industrial Power Supply

Accessories

			
NDR-240-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/240W -20°C ~ 70°C	MDR-10-12 Indoor Industrial Din-Rail Power Supply, 12 V AC/DC/10W -20°C ~ 70°C	MDR-40-48 Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W -20°C ~ 70°C	**CH-110-V2** • 19'', 1U 8-bay rack mount chassis • For M31-011-01 use

Gigabit PoE Injector

Indoor Gigabit 60W/90W/95W PoE Injector

Outdoor IP67/IK10 Gigabit 60W/90W/95W PoE Injector

Industrial Gigabit 90W/95W PoE Injector









Gigabit PoE Injector

60W bt PoE | 60W PoH PoE | 90W bt PoE | 95W PoH PoE

PoE Injector Gigabit

- Indoor
  -  I36-210 P37
  -  I36-200 P37
  -  I39-210 P37
  -  I39-200 P37
- Outdoor IP67/IK10
  -  I46-210 P37
  -  I46-200 P37
  -  I46-201-A P37
  -  I49-210 P38
  -  I49-200 P38
  -  I49-201-A P38
- Industrial
  -  I69-210 P38
  -  I69-216 P38
  -  I69-200 P38
  -  I69-206 P38

I36 Series - Indoor Gigabit 60W PoE Injector



I36-200

Features

- 60W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- IEEE 802.3at/af compliant
- 100~240VAC input power




I36-210

Features

- 60W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- IEEE 802.3bt/at/af compliant
- 100~240VAC input power

Applications



I39 Series - Indoor Gigabit 90W/95W PoE Injector



I39-200

Features

- 95W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- IEEE 802.3at/af compliant
- 100~240VAC input power




I39-210

Features

- 90W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- IEEE 802.3bt/at/af compliant
- 100~240VAC input power

Applications



I46 Series - IP67/IK10 Gigabit 60W PoE Injector



I46-200

Features

- IP67, IK10, -40°C~65°C
- 60W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 100~240VAC input power



I46-201-A

Features

- IP67, IK10, -40°C~65°C
- 60W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- For Avigilon PTZ/IR PTZ/Multisensor
- 100~240VAC input power





I46-210

Features

- IP67, IK10, -40°C~65°C
- 60W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 100~240VAC input power

Applications





Gigabit PoE Injector

I49 Series - IP67/IK10 Gigabit 95W PoE Injector



I49-200

Features

- IP67, IK10, -40°C ~ 65°C
- 95W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 100~240VAC input power



I49-201-A

Features

- IP67, IK10, -40°C ~ 65°C
- 95W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- For Avigilon PTZ/IR PTZ/Multisensor
- 100~240VAC input power




I49-210

Features

- IP67, IK10, -40°C ~ 65°C
- 90W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 100~240VAC input power

Applications



I69 Series - Industrial Gigabit 90W/95W PoE Injector



I69-200

Features


- -40°C ~ 75°C operating temperature
- 95W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 48~56VDC input power



I69-210

Features

- -40°C ~ 75°C operating temperature
- 90W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 48~56VDC input power



I69 Series - Industrial Gigabit 90W/95W PoE Injector w/ 12~56VDC Input



I69-206

Features


- -40°C ~ 75°C operating temperature
- 95W PoH PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 12~56VDC input power



I69-216

Features

- -40°C ~ 75°C operating temperature
- 90W bt PoE output
- 6KV PoE surge protection
- Supports 10/100/1000Mbps data rates
- 12~56VDC input power



Related Products

Pole Mount	Corner Mount		Junction Box
 AT-100 Pole Mount Adapter	 AT-101 Pole Mount Adapter	 AT-200 Corner Mount Adapter	 JB-200 Junction Box

Industrial Power Supply				
 NDR-75-48 Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W -20°C ~ 70°C	 NDR-120-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/120W -20°C ~ 70°C	 NDR-240-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/240W -20°C ~ 70°C	 NDR-480-48 Indoor Industrial Din-Rail Power Supply, 48~55VDC/480W -20°C ~ 70°C	 MDR-10-12 Indoor Industrial Din-Rail Power Supply, 12 V AC/DC/10W -20°C ~ 70°C

Industrial Power Supply				
 MDR-40-48 Indoor Industrial Din-Rail Power Supply, 48 V AC/DC/40W -20°C ~ 70°C	 HLG-120H-54 Outdoor Industrial Power Supply 54VDC/120W -40°C ~ 70°C, IP67	 HLG-240H-54 Outdoor Industrial Power Supply 54VDC/240W -40°C ~ 70°C, IP67	 DRL-48V120W1EN Indoor Industrial Din-Rail Power Supply 48V, 120W	 DRL-48V240W1EN Indoor Industrial Din-Rail Power Supply 48V, 240W

Gigabit PoE Extender

Indoor Gigabit 90W PoE Extender

Outdoor IP67/IK10 Gigabit 90W PoE Extender

Indoor Gigabit 90W PoE Extender Plus

Outdoor IP67/IK10 Gigabit 90W PoE Extender Plus








Gigabit PoE Extender

90W bt PoE | 90W bt PoE w/ Voltage Booster



E59 Series - Indoor Gigabit 90W PoE Extender




E59-101

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 1-port Gigabit Passive PoE output (Compliant 802.3af)
- 6KV Surge protection
- Drives the reach beyond restricted 100m Ethernet distance

Application






E59-102

Features

- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 2-port Gigabit Passive PoE output (Compliant 802.3af)
- 6KV Surge protection
- Drives the reach beyond restricted 100m Ethernet distance

Application



E69 Series - Outdoor IP67/IK10 Gigabit 90W PoE Extender




E69-101

Features

- **IP67, IK10, -40°C~65°C**
- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 1-port Gigabit Passive PoE output (Compliant 802.3af)
- 6KV Surge protection
- Operating temperature: -40°C ~ 65°C
- Drives the reach beyond restricted 100m Ethernet distance

Application






E69-102

Features

- **IP67, IK10, -40°C~65°C**
- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 2-port Gigabit Passive PoE output (Compliant 802.3af)
- 6KV Surge protection
- Operating temperature: -40°C ~ 65°C
- Drives the reach beyond restricted 100m Ethernet distance

Application



Gigabit PoE Extender

E69 Series - Outdoor IP67/IK10 IEEE 802.3bt PoE++ to IEEE 802.3af/at/bt PoE++ Extender




E69-201

Features

- **IP67, IK10, -40°C ~ 65°C**
- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 1-port Gigabit **802.3af/at/bt PoE++ output**
- IEEE 802.3af/at/bt compliant
- 6KV Surge protection
- Operating temperature: -40°C ~ 65°C
- Drives the reach beyond restricted 100m Ethernet distance

Application






E69-202

Features

- **IP67, IK10, -40°C ~ 65°C**
- 1-port Gigabit **30W/60W/90W bt PoE++ input** + 2-port Gigabit **802.3af/at/bt PoE++ output**
- IEEE 802.3af/at/bt compliant
- 6KV Surge protection
- Operating temperature: -40°C ~ 65°C
- Drives the reach beyond restricted 100m Ethernet distance

Application



E59 Series - Indoor Gigabit 90W PoE Extender Plus




E59-602

Features

- **Voltage Booster**
- 1-port Gigabit **30W/60W/90W bt PoE input** + 1-port Gigabit 56VDC Passive PoE output + (Compliant 802.3af PoE)
  1-port Gigabit **24VDC or 56VDC** Passive PoE output
- Drives the reach beyond restricted 100m Ethernet distance

Application



E69 Series - Outdoor IP67/IK10 Gigabit 90W PoE Extender Plus





E69-602

Features

- IP67, IK10, -40°C ~ 65°C
- **Voltage Booster**
- 1-port Gigabit **30W/60W/90W bt PoE input** + 1-port Gigabit 56VDC Passive PoE output + (Compliant 802.3af PoE)
  1-port Gigabit **24VDC or 56VDC** Passive PoE output
- Drives the reach beyond restricted 100m Ethernet distance

Application





Fiber — PoE (Data + Power) — 24VDC PoE (Data + Power)

Gigabit PoE Surge Protector

1-CH Gigabit 802.3 bt/at/af PoE Surge Protector

4-CH/24-CH Gigabit 802.3 bt/at/af PoE Surge Protectors

4-CH/24-CH IP Managed Gigabit 802.3 bt/at/af PoE Surge Protectors












Gigabit PoE Surge Protector

1G/2.5Gbps | 10Gbps | 1G/2.5Gbps Modulars



SD Series - Indoor Gigabit 90W/95W PoE Surge Protector



SD-101

Features

- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Failure LED indicator
- Operating temperature between -40°C to 85 °C




SD-102

Features

- Supports 10M/100M/1G/2.5G/10G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Failure LED indicator
- Operating temperature between -40°C to 85 °C

Applications



SD Series - Outdoor IP67/IK10 Gigabit 90W/95W PoE Surge Protector



SD-201

Features

- **IP67, IK10, -40°C ~ 85°C**
- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Failure LED indicator
- Operating temperature between -40°C to 85 °C




SD-202

Features

- **IP67, IK10, -40°C ~ 85°C**
- Supports 10M/100M/1G/2.5G/10G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Failure LED indicator
- Operating temperature between -40°C to 85 °C

Applications



Gigabit PoE Surge Protector

SD Series - Modular Gigabit 90W/95W PoE Surge Protector



SD-404

Features

- 4-CH PoE Surge Protectors
- Din-rail installation, Slide-in modular design
- Quick swap when Lifetime of single PoE surge module is expired
- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Operating temperature between -40°C to 85 °C



SD-424

Features

- 24-CH PoE Surge Protectors
- 1U,19" Rack Mount, Slide-in modular design
- Quick swap when Lifetime of single PoE surge module is expired
- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Operating temperature between -40°C to 85 °C

SD Series - IP Managed Modular Gigabit 90W/95W PoE Surge Protectors



SD-504

Features

- Web UI Setup & lifetime detection
- Alarm log event
- 4-CH PoE Surge Protectors
- Quick swap when lifetime of single PoE surge module is expired
- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Operating temperature between -40°C to 75 °C




SD-524

Features

- Web UI Setup & lifetime detection
- Alarm log event
- 24-CH PoE Surge Protectors
- Quick swap when life time of single PoE surge module is expired
- Supports 10M/100M/1G/2.5G bps Ethernet
- Supports 802.3af / 802.3at / 802.3bt
- Protects up to 20KV / 10KA surge
- Operating temperature between -40°C to 75 °C


Applications

Remote side




SD-404 or SD-504
PoE Surge Protector

Center Side



IP Managed Surge Protector







Related Product



CH-110-V2

- 19", 1U 8-bay rack mount chassis
- For 8 pieces of SD-101/SD-102



Outdoor Surveillance system Product Guide

Back-up PoE Cabinet

IP Back-up PoE Cabinet

Outdoor Back-up PoE Cabinet

Back-up PoE Cabinet - OS-100-250


Features

- Redundant Battery Backup Power System
- Compact design / IP66 rated
- Output 54VDC voltage for PoE device use
- Space for PoE switch / PoE Surge protector installation
- Include Thermal Switch control heater and blower
- Battery protection for deep discharge and short circuit
- Space for 12V/7Ah Battery x 4PCS


Redundant Battery Backup Power System

OS-100-250 a 250W power supply charger, converts 100~240VAC input into a 54VDC for IP PoE device

250W AC power built-in charger for sealed lead acid battery.



Application



Outdoor IP Back-up PoE Cabinet

IP Back-up PoE Cabinet - OS-200 Series


H/W Features


- •100~240V AC input power 240W Power supply (OS-200-240)
- •100~240V AC input power 480W Power supply (OS-200-480)
- •Simple Pole mount and wall mount installations
- •IP66 rated
- •a wide variety of DC output power
  - •12V/24V/dual 56V DC output in outside AC power is normal
  - •continuous 12/24/dual 5QV DC output if the AC input fails over - Built-in IP POE

S/W Features


- •SNMP MIB for integration with Network management systems
- •SNMP trap triggers to notify once the monitoring status is abnormal.
- •Unified monitoring status:
  - •battery
  - •DC output
  - •blower
  - •temperature, and humidity
- •Unified controlling
  - •battery on/off
  - •heater & blower
  - •rebooting DC output power

Application





OS-200 Series-System Dash-Board




OS-200 Series-Notification




OS-200 w/ D60 Series L2 Pro PoE Switch NTS Page

Topology View



Map View



Related Product

Din-Rail Industrial L2 PRO Gigabit Ethernet PoE Switch



D60-044-30
4xGbE PoE (30W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D60-044-90
4xGbE bt/PoH PoE (90W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D60-044-91
4xGbE bt PoE (90W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D60-084-30
8xGbE PoE (30W) +
4xGbE SFP
48~56VDC Input

PoE Surge Protectors



SD-404
802.3af/802.3at/802.3bt/UPoE
4-CH PoE Surge Protectors

PoE Surge Protectors



SD-504
802.3af/802.3at/802.3bt/UPoE
4-CH PoE Surge Protectors

Din-Rail Industrial Gigabit PoE Switches



D40-044-30
4xGbE 30W PoE +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D40-044-91
4x 90W bt PoE +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D40-082-30
8xGbE 30W PoE +
2xGbE SFP
48~56VDC Input

Din-Rail Industrial L2 Gigabit Ethernet PoE Switch



D51-044-30
4xGbE PoE (30W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D51-044-90
4xGbE bt/PoH PoE (90W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D51-044-91
4xGbE bt PoE (90W) +
2xGbE SFP +
2xGbE RJ45
48~56VDC Input



D51-084-30
8xGbE PoE (30W) +
4xGbE SFP
48~56VDC Input

Din-Rail Industrial Gigabit PoE Media Converter



M30-011-30
1-port Gigabit 30W PoE +
1-port Gigabit SFP



M30-022-91
2-port Gigabit 90W bt PoE +
2-port Gigabit SFP

Din-Rail Industrial PoE Injector



I69-210-V2
Industrial GbE 90W bt
PoE Injector
48~56VDC Input



I69-216-V2
Industrial GbE 90W bt
PoE Injector
12~56VDC Input

Din-Rail Industrial PoE Splitter



S69-210-V2
Industrial GbE 90W bt
PoE Splitter
48~56VDC Input

Camera Housing
Product Guide

AI Camera Housing
AC24V(Optional DC24V)
802.3 bt/at/af PoE
800m PoE
AISI 316L Stainless Steel





Camera Housing Product Selection

AC24V | 30W PoE | 90W PoE | EPoC | EPoT

Aluminum IP66 / 68 IK10

- Heater & Blower — Unmanaged
  - A1000 P54 | A5000 P54 | A5000-E P56 | A5000-T P57
- Heater & Blower Fixed IR 50m — Unmanaged
  - A1020 P54 | A5020 P54 | A5020-E P56 | A5020-T P57
- Heater & Blower VAIR — Unmanaged
  - P2000-I P53 | P6000-I-V2 P53
- Heater & Blower VAIR — AI
  - M2000-I P51 | M6000-I P52
- Heater & Blower Temp.-50°C VAIR — Unmanaged
  - P2000-AI P53
- Heater & Blower Temp.-50°C VAIR — AI
  - M2000-AI P51 | M6000-AI P52
- Heater & Blower Wiper VAIR — Unmanaged
  - P2000-IW P53 | P6000-IW P53
- Heater & Blower Wiper VAIR — AI
  - M2000-IW P51 | M6000-IW P52
- Heater & Blower VAIR Wiper Temp.-50°C — Unmanaged
  - P2000-AIW P53
- Heater & Blower VAIR Wiper Temp.-50°C — AI
  - M2000-AIW P51 | M6000-AIW P52
- Thermal — Unmanaged
  - A2100 P50 | A5100 P50 | A5100-E P56 | A5100-T P57

316L Stainless Steel IP66 / IP68 IK10

- Heater & Blower — Unmanaged
  - S1000 P58 | S5000 P58 | S5000-E P58 | S5000-T P58
- Heater & Blower 12W VAIR LED — Unmanaged
  - S2000-I P58 | S6000-I P58 | S5000-EI P58 | S5000-TI P58
- Heater & Blower 12W VAIR LED Built-in wiper — Unmanaged
  - S2000-IW P58 | S6000-IW P58
- Thermal — Unmanaged
  - S2100 P59 | S5100 P59 | S5100-E P58 | S5100-T P58

AI Camera Housing – AC24V input

M2000 AI Camera Housing – AC24V input



M2000-I

Features
- IP68 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V input
- Aluminum die casting body



M2000-IW

Features
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V input
- Aluminum die casting body



M2000-AI


Features
- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- IP68 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V input
- Aluminum die casting body




M2000-AIW

Features
- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V input
- Aluminum die casting body

AI Camera Housing Managed UI



Application



AI Camera Housing – PoE input (90W bt & 95W PoH)

M6000 AI Camera Housing – PoE input (90W bt & 95W PoH)



M6000-I

Features

- IP68 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- 90W bt & 95W PoH PoE input
- Optional VAIR Illuminator
- Aluminum die casting body



M6000-IW

Features

- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- 90W bt & 95W PoH PoE input
- Optional VAIR Illuminator
- Aluminum die casting body



M6000-AI

Features

- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- IP68 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- 90W bt & 95W PoH PoE input
- Aluminum die casting body




M6000-AIW


Features

- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Web UI Control
- Window heater & blower
- Adjustable sunshield
- 90W bt & 95W PoH PoE input
- Aluminum die casting body

AI Camera Housing Managed UI



Plug-and-Play quick connection for PoE IP box/brick camera inside smart camera housing



Professional Camera Housing

P20 Series - Professional AC24V Camera Housing



P2000-I

Features

- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V Input (Optional DC24V)
- Aluminum die casting body



P2000-AI

Features

- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V Input (Optional DC24V)
- Aluminum die casting body



P2000-IW

Features

- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V Input (Optional DC24V)
- Aluminum die casting body



P2000-AIW

Features

- **Arctic cold start heater at -40°C (operating temperature at -50°C)**
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- Optional VAIR illuminator
- AC24V Input (Optional DC24V)
- Aluminum die casting body

P60 Series - Professional 90W bt PoE Camera Housing



P6000-I-V2

Features

- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- 90W bt PoE input
- Optional VAIR Illuminator
- Aluminum die casting body



P6000-IW


Features

- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- 90W bt PoE input
- Optional VAIR Illuminator
- Aluminum die casting body


Professional Camera Housing Line	
P20 Series	P60 Series
AC24V Input	90W bt PoE Input
- ITB(Illuminator Touch Board) for optional Vair-IR illuminator - Quick latch & tether wire for safety installation - Side opening alarm interface - Adjustable sunshield	- Spacious dimensions for camera equipped with long varifocal lens - Window heater for demisting & deicing - Blower - Aluminum die casting body
- Optional wiper - Optional cold start heater	- Optional VAIR illuminator - Optional water tank & pump
- I : ITB(Illuminator touch board) - A: Arctic cold start heater at -40°C (operating temperature -50°C)	- W: Wiper

VAIR Illuminator Technology


VAIR technology is an optical technology to adjust illuminator beam angle by remote control thru RS485 Pelco-D command or manual dip switch to suit camera FOV




Without exposing power cable & RS485 wire for illuminator



Safety tether wire & Quick latch for safety installation



VR-120	VR-241	VR-481
Snap-in 12W IR LEDs	Snap-in 24W IR LEDs	Snap-in 48W IR LEDs



Affordable / Thermal / ANPR Camera Housing

A10 Series - Affordable Camera Housing



A1000

Features
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- AC24V/DC24V input
- Aluminum die casting body



A1020

Features
- **6W Fixed IR viewing up to 50m**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- AC24V/DC24V input
- Aluminum die casting body

A50 Series - Affordable PoE Camera Housing



A5000

Features
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- 30W at PoE input
- Aluminum die casting body



A5020

Features
- **6W Fixed IR viewing up to 50m**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- 30W at PoE input
- Aluminum die casting body

A21 Series - Thermal Camera Housing Line



A2100

Features
- AC24V/DC24V input
- **Germanium window**
- Blower
- IP68/IK10
- Aluminum die casting body

A51 Series - Thermal PoE Camera Housing Line



A5100

Features
- 30W at PoE input
- **Germanium window**
- Blower
- IP68/IK10
- Aluminum die casting body

P29_P69 Series - ANPR Camera Housing



P2900-IW Kit A

Features
- **Catch speed up to 100km/h**
- IP66 rated, IK10 vandal proof
- AC24V input
- Built-in wiper
- 48W VAIR Illuminator
- Aluminum die casting body



P6900-IW Kit A

Features
- **Catch speed up to 100km/h**
- IP66 rated, IK10 vandal proof
- 90W bt PoE input
- Built-in wiper
- 48W VAIR Illuminator
- Aluminum die casting body

P29 Kit A/B Series - ANPR Camera Housing



P2915 Kit A/B


Features
- **Catch speed up to 150km/h**
- IP68 rated, IK10 vandal proof
- 90W External VAIR Illuminator
- AC24V input
- Aluminum die casting body



P2925 Kit A/B

Features
- **Catch speed up to 250km/h**
- IP68 rated, IK10 vandal proof
- 288W pulse mode external VAIR Illuminator
- DC24V input
- Aluminum die casting body

Dimensions





Accommodate with AXIS Q1635 + 8-80mm vari-focal lens



Accommodate with Avigilon H4A/H5A box & H4 Pro/H5A Pro box equipped with long range van-focal lens

Related Products

Brackets

Wall Mount



BK-101
Wall Mount Bracket
Safety Wire
Concealing Cable



BK-102
Wall Mount Bracket
Concealing Cable

Ceiling Mount



BK-200
J-type
Ceiling Mount Bracket



BK-201
Flexible J-type
Ceiling Mount Bracket

Standing Mount



BK-300
Standing Mount Bracket

Adapters

Pole Mount



AT-100
Pole Mount Adapter



AT-101
Pole Mount Adapter

Corner Mount



AT-200
Corner Mount Adapter

Fit



BK-101



BK-102

Junction Box

Wall Mount



JB-100
Junction Box

Fit



BK-101



BK-102



AT-100



AT-101

AT-200

VAIR LEDs

VAIR LEDs (For -I model)



VR-120
- Snap Vair 10~40° IR LED, 12W



VR-241
- Snap Vair 10~30° IR LED, 24W

VR-481
- Snap Vair 10~30° IR LED, 48W

Water Tank & Pump

Water Tank & Pump (For -W model)



TP-100
- 10L Water Tank & Pump

Power Boxes

Model Name	 A10 Series	 P20 Series	 P29 Series	 M20 Series
 **PB-024-1AC** • IP67/IK10 • 115VAC / 230VAC Input • 24VAC/6A Output				
 **PB-024-2AC** • IP67/IK10 • 115VAC / 230VAC Input • 24VAC/6A Output • For BK-101 & BK-102				

PoE Switches

Model Name	 A50 Series	 P60 Series	 P69 Series	 M60 Series
30W PoE Switch 		–	–	–
90W PoE Switch 	–			

800m PoE Camera Housing over Coax

800m PoE Camera Housing over Coaxial Cable



A5000-E

Features
- IP68 rated, IK10 vandal proof
- Window heater & blower
- EPoC Input
- 6KV surge protector
- Aluminum die casting body



A5020-E


Features
- **6W Fixed IR viewing up to 50m**
- IP66 rated, IK10 vandal proof
- EPoC Input
- 6KV surge protector
- Aluminum die casting body



A5100-E

Features
- **Germanium window**
- IP68 rated, IK10 vandal proof
- EPoC Input
- 6KV surge protector
- Aluminum die casting body

Applications



Related Products

EPoC RX Adapter Series



XE10-110-RX
- XE10-110-RX EPoC adapter (RX)
- 65W@56VDC power adapter



XE11-110-RX
- XE11-110-RX PoE EPoC adapter (RX)
- Supports 30W/60W/90W PoE Input

EPoC RX Switch



XC10-041-250
- 4xBNC coaxial ports, 1xGigabit LAN port
- Playing RX mode
- 6KV surge protection for each EPoC port
- 250W Power Supply, 100~240VAC input



XC10-084-380
- 8xBNC coaxial ports & 4xGigabit LAN port
- Playing RX mode
- 6KV surge protection for each EPoC port
- 380W Power Supply, 100~240VAC input

EPoC Related Product



CH-100-V2
- 19", 1U 4-bay Rack Mount Chassis
- For 4 sets of XE10-110-RX & 65W power adapter



D40-044-91
- 60W/90W bt PoE Switch
- Works with XE11-110-RX



SD-301
- BNC Surge Protector
- 6KV Surge Protection



BNC-Y
- Y-Type BNC Adapter



CH-110-V2
- 19", 1U 8-bay rack mount chassis
- For 8 pieces of XE11-110-RX



I39-210
- 90W bt PoE Injector
- Works with XE11-110-RX



BNC-T
- T-Type BNC Adapter



BNC-YC
- Outdoor Y-Type BNC Cable

Brackets

Wall Mount



BK-101
Wall Mount Bracket
Safety Wire
Concealing Cable



BK-102
Wall Mount Bracket
Concealing Cable

Ceiling Mount



BK-200
J-type
Ceiling Mount
Bracket



BK-201
Flexible J-type
Ceiling Mount
Bracket

Standing Mount



BK-300
Standing Mount
Bracket

Adapters

Pole Mount



AT-100
Pole Mount Adapter



AT-101
Pole Mount Adapter

Corner Mount



AT-200
Corner Mount Adapter

Fit



BK-101



BK-102

Junction Box

Wall Mount



JB-100
Junction Box

Fit

BK-101



BK-102



AT-100



AT-101

AT-200

800m PoE Camera Housing over UTP/STP

800m PoE Camera Housing over Cat.5e / Cat.6 Cable



A5000-T

Features

- IP68 rated, IK10 vandal proof
- Window heater & blower
- EPoT Input
- 6KV surge protector
- Aluminum die casting body



A5020-T

Features

- **6W Fixed VAIR viewing up to 50m**
- IP66 rated, IK10 vandal proof
- EPoT Input
- 6KV surge protector
- Aluminum die casting body




A5100-T

Features

- **Germanium window**
- IP68 rated, IK10 vandal proof
- EPoT Input
- 6KV surge protector
- Aluminum die casting body

Applications



Related Products

EPoT RX Adapter Series



TE10-110-RX

- TE10-110-RX EPoT adapter (RX)
- 65W @56VDC power adapter



TE11-110-RX

- TE11-110-RX PoE EPoT adapter (RX)
- Supports 30W/60W/90W PoE Input

EPoT Related Product



D40-044-91

- 60W/90W bt PoE Switch
- Works with XE11-110-RX



I39-210

- 90W bt PoE Injector
- Works with XE11-110-RX



UTP-YC cable

- Outdoor Y type RJ45 Cable



CH-100-V2

- 19", 1U 4-bay rack mount chassis
- For 4 sets of TE10-110-RX & 65W power adapter



CH-110-V2

- 19", 1U 8-bay rack mount chassis
- For 8 pieces of TE11-110-RX

Brackets

Wall Mount



BK-101
Wall Mount Bracket
Safety Wire
Concealing Cable



BK-102
Wall Mount Bracket
Concealing Cable

Ceiling Mount



BK-200
J-type
Ceiling Mount Bracket



BK-201
Flexible J-type
Ceiling Mount Bracket

Standing Mount



BK-300
Standing Mount Bracket

Adapters

Pole Mount



AT-100
Pole Mount Adapter



AT-101
Pole Mount Adapter

Corner Mount



AT-200
Corner Mount Adapter

Fit



BK-101



BK-102

Junction Box

Wall Mount



JB-100
Junction Box

Fit



BK-101



BK-102



AT-100



AT-101

AT-200

AISI 316L Stainless Steel Camera Housing

AC24V Camera Housing



S1000

Features
- IP68 rated, IK10 vandal proof
- AC24V/DC24V input
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S2000-I

Features
- **12W VAIR LED**
- IP66 rated, IK10 vandal proof
- AC24V Input
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S2000-IW

Features
- **12W VAIR LED**
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- AC24V Input
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments

PoE Camera Housing



S5000

Features
- 30W at PoE Input
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S6000-I

Features
- 90W bt PoE input
- **12W VAIR LED**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S6000-IW

Features
- 90W bt PoE input
- **12W VAIR LED**
- **Built-in wiper**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments

600m PoE over Coaxial Cable Camera Housing



S5000-E

Features
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- EPoC Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S5000-EI

Features
- **12W VAIR LED**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- EPoC Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S5100-E

Features
- **Germanium window**
- IP68 rated, IK10 vandal proof
- Blower
- Adjustable sunshield
- EPoC Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments

600m PoE over UTP/STP Cable Camera Housing



S5000-T

Features
- IP68 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- EPoT Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S5000-TI

Features
- **12W VAIR LED**
- IP66 rated, IK10 vandal proof
- Window heater & blower
- Adjustable sunshield
- EPoT Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments



S5100-T

Features
- **Germanium window**
- IP68 rated, IK10 vandal proof
- Blower
- Adjustable sunshield
- EPoT Input
- AISI 316L stainless steel construction
- Fits corrosive & severe environments

AISI 316L Stainless Steel Camera Housing

Thermal Camera Housing Line



S2100

Features

- **Germanium window**
- IP68 rated, IK10 vandal proof
- AC24V/DC24V input
- Blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments




S5100

Features


- **Germanium window**
- IP68 rated, IK10 vandal proof
- 30W at PoE Input
- Blower
- Adjustable sunshield
- AISI 316L stainless steel construction
- Fits corrosive & severe environments


VAIR Illuminator Technology

VAIR technology is an optical technology to adjust illuminator beam angle by remote control thru RS485 Pelco-D command or manual dip switch to suit camera FOV




Wide angle for short distance








Tele angle for long distance




AISI 316L Stainless Steel Dimensions









Related Products

Wall Mount Bracket



BK-103
AISI 316L Stainless Steel
Wall Mount Bracket

Water Tank & Pump (For -W model)



TP-100
Stainless Steel
10L Water Tank & Pump

Pole Mount



AT-102
AISI 316L Stainless steel
Pole Mount Adapter

Professional Illuminators for Security Lighting.









Illuminators
Product Guide

Manual
Motor
Pulse Mode
Affordable

Professional Illuminators

2 Easy Configuration
- 4 LED ON/OFF Control Modes
- Adjustable Light Sensor Sensitivity
- Support Pelco D via RS485 Interface

3 Smart Protection
- LED High Temp Self-protection
- Diagnostic

4 Reliable Casing
- Solid Particle Protection IP6X
- Liquid Ingress Protection IPX6/IPX8
- Impact Protect IK10

5 Beam Angle Adjust
- Fix Angle
- Manual Tech
- Motor Tech

Professional - Manual Adjustable Beam Angle



VR-486-1040

Features
- 48W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 10°~40°
- Capture range: 100~250m (590~850ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VR-486-2040

Features
- 48W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 20°~40°
- Capture range: 120~200m (393~656ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VR-486-4080

Features
- 48W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 40°~80°
- Capture range: 60~90m (196~295ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VR-486-90120

Features
- 48W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 90°~120°
- Capture range: 44~55m (147~180ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VR-486-180

Features
- 48W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 180°
- Capture range: 0~40m (0~131ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VW-486-1040

Features
- 48W Fixed IR viewing over White Light 5000K
- Beam angle: 10°~40°
- Capture range: 100~250m (590~850ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VW-486-2040

Features
- 48W Fixed IR viewing over White Light 5000K
- Beam angle: 20°~40°
- Capture range: 120~200m (393~656ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VW-486-4080

Features
- 48W Fixed IR viewing over White Light 5000K
- Beam angle: 40°~80°
- Capture range: 60~90m (196~295ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VW-486-90120

Features
- 48W Fixed IR viewing over White Light 5000K
- Beam angle: 90°~120°
- Capture range: 45~55m (147~180ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power

Professional - Motor Adjustable Beam Angle



VR-806-1040

Features
- 90W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 10°~40°
- Capture range: 140~350m (459~1148ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power



VR-806-2040

Features
- 90W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 20°~40°
- Capture range: 170~280m (557~918ft)
- IP66, IP68 rated, IK10 vandal proof
- 24VAC or 24VDC input power

Professional - Pulse Mode



VR-246-1040


Features
- 24W (288W Puise Mode Power) over IR 850nm lighting source
- IP66, IP68 rated, IK10 vandal proof
- 24VDC input power



VR-246-2040

Features
- 24W (288W Puise Mode Power) over IR 850nm lighting source
- IP66, IP68 rated, IK10 vandal proof
- 24VDC input power

Angle Adjust



Professional Illuminators

Affordable-Fixed Beam Angle



FR-326-010

Features
- 32W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 10°
- Capture range: 0~180m (0~590ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FR-326-035

Features
- 32W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 35°
- Capture range: 0~60m (0~196ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FR-326-070

Features
- 32W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 70°
- Capture range: 0~35m (0~114ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FR-326-100

Features
- 32W Fixed IR viewing over IR 850nm lighting source
- Beam angle: 100°
- Capture range: 0~25m (0~85ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FW-326-010

Features
- 32W Fixed IR viewing over White Light 5000K
- Beam angle: 10°
- Capture range: 0~180m (0~590ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FW-326-035

Features
- 32W Fixed IR viewing over White Light 5000K
- Beam angle: 35°
- Capture range: 0~60m (0~196ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FW-326-070

Features
- 32W Fixed IR viewing over White Light 5000K
- Beam angle: 70°
- Capture range: 0~35m (0~114ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power



FW-326-100

Features
- 32W Fixed IR viewing over White Light 5000K
- Beam angle: 100°
- Capture range: 0~25m (0~85ft)
- IP66 rated, IK10 vandal proof
- 24VAC or 24VDC input power

Security Lighting & LPR Lighting Applicaitons



Long Distance




Panoramic Lighting




Generic View



LPR Solution



Continuous Mode



Pulse Mode

AETEK INC.
10F, No.168, Lien-Cheng Rd., Chung-Ho,New Taipei City, 235, Taiwan, R.O.C
+886-2-82452822 sales@aetektec.com www.aetektec.com

AETEK INC. Specifications are subject to change without notice. AETEK is registered trademark of AETEK INC. and its overseas subsidiaries. All other trademarks belong to their respective owners.

Copyright © AETEK INC. All rights reserved. July, 2022